

## RADIATION

### Brightness Transmitter

Part number: 7.1414.22.xxx

The linearized electrical output signal can be used for the control of shading devices, heating systems, and irrigation plants.



### Specification

Part number: 7.1414.22.xxx

#### Brightness

Measuring range	0 ... 2 kLux
Spectral range	420 ... 675 nm
Accuracy	±3 % of meas. range
Acquisition angle elevation	±55 °

#### General

Power supply	24 V AC/DC
Ambient temp.	-30 ... +70 °C
Electr. connection	clamp connection, screwed cable gland
Protection	IP 65
Dimension	80 x 82 x 65 mm
Weight	0.15 kg

### Versions

As per 7.1414.22.xxx, but:

Product number 7.1414.22.040

#### Brightness

Electrical output	0 ... 20 mA
-------------------	-------------

Product number 7.1414.22.041

#### Brightness

Electrical output	4 ... 20 mA
-------------------	-------------






Product number 7.1414.22.061

**Brightness**

Electrical output 0 ... 10 V

## Accessories

Product	Product name	Brief description
	Hanger 1 m ( for radiation sensors ) 4.3185.xx.009	The hanger is used for laterally mounting of a radiation- or brightness transmitter onto a mast. <b>General</b> Length 1 m Material Aluminium Tube diameter Ø 50 mm Weight 1.8 kg
	Adapter Compact 506345	The adapter serves for mounting a radiation transmitter, baro transmitter or brightness transmitter onto a traverse (4.3171.30.000, 4.3171.40.000) or holder (506 347). <b>General</b> Material Aluminium, anodized Dimension 100 x 115 x 65 mm Weight 0.5 kg
	Adapter Compact 0 ... 90 ° adjustable 508850	The adapter serves for mounting a radiation transmitter, baro transmitter or brightness transmitter onto a traverse (4.3171.30.000, 4.3171.40.000) or holder (506 347). <b>General</b> Material Aluminium, anodized Dimension 100 x 115 x 65 mm Weight 0.5 kg Function 0 ... 90 ° adjustable

