

## WIND

### Clima Sensor D

**Part number: 4.91xx.00.061**

These are available as

- Serial RS 485/422

telegram and as

- Analogue outputs

for further processing

The CLIMA Sensor D has an internal DCF77 receiver, which takes the time signal of an atomic clock, and integrates it into the data telegram.

Ranges of application are:

- Building control systems
- Control technique
- Green house technique
- Processing of the acquired

data to recording or display instruments.

Depending on the model, the following data can be measured by the Clima Sensor D:

- Wind velocity
- Precipitation (yes/no)
- Brightness in Eastern, Southern and Western direction
- Twilight
- Temperature
- Rel. humidity

The respective holder serves for the mounting at masts or plane surfaces, depending on the range of application. Instrument with internal condensation shield



## Specification

**Part number: 4.91xx.00.061**

### Precipitation

Measuring range	yes / no
Switch-off-delay	approx. 2 min
Sensitivity	fine drizzle

### Brightness

Measuring range	0 ... 150 kLux
Spectral range	700 ... 1050 nm
Accuracy	±10 % vom rel. Messwert
Measured directions	South, East, West

### Twilight

Measuring range	0 ... 250 Lux
Spectrum range	700 ... 1050 nm
Accuracy	±10 % of meas. value

### Data output digital

Interface	RS485 / RS422
Baudrate	1200 ... 19200 Baud



Duplex mode	Full / halfduplex
Protocol	ASCII
Parameter	environmental data, housing temperature, date / time, sensor status, checksum
<b>Data output analog</b>	
Type	max. 8 x 0 ... 10V (incl. Precipitation: 0 or 10 V)
Voltage output	min. 10 k
<b>General</b>	
Power supply	16 ... 28V DC or 16 ... 24 V AC, max. 150 mA
Current consumpt.	600 mA
Electr. connection	10 m cable, LiYCY 16 x 0.14 mm <sup>2</sup> , UV - resistant
Mounting	Wall or mast mounting, retaining clamb, stainless steel
Weight	1.5 kg

## Versions

As per 4.91xx.00.061, but:

### Product number 4.9100.00.061

<b>Wind speed</b>	
Measuring range	1 ... 40 m/s
Accuracy	±0.5 m/s or ±5 % of meas. range
<b>General</b>	
Dimension	Ø 130 x 335 mm
Weight	1.5 kg

### Product number 4.9101.00.061

<b>General</b>	
Dimension	Ø 130 x 215 mm
Weight	1.5 kg

### Product number 4.9110.00.061

<b>Wind speed</b>	
Measuring range	1 ... 40 m/s
Accuracy	±0.5 m/s or ±5 % of meas. range



#### Temperature

Measuring range	-20 ... +60 °C
Accuracy	±0,5 K @ WS > 2.5 m/s
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B

#### Rel. Humidity

Measuring range	0 ... 100 % rel. h.
Accuracy	± 3% rel. h. (@ 10 ... 90 % rel. h. and WS > 2.5 m/s)

#### General

Dimension	Ø 130 x 430 mm
Weight	1.5 kg

#### Product number 4.9111.00.061

#### Temperature

Measuring range	-20 ... +60 °C
Accuracy	±0,5 K @ WS > 2.5 m/s
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B

#### Rel. Humidity

Measuring range	0 ... 100 % rel. h.
Accuracy	± 3% rel. h. (@ 10 ... 90 % rel. h. and WS > 2.5 m/s)

#### General

Dimension	Ø 130 x 310 mm
Weight	1.5 kg

## Accessories

No accessories are available for this product.

