

TEMPERATURE

Hygro-Thermo Transmitter compact

Part number: 1.1005.54.7xx

The data are output as electrical analogue signals The transmitters consist of a capacitive humidity element and a Pt 100 resistance thermometer. For outdoor installation we recommend the use of the weather- and thermal radiation shield.

Order no.: 1.1025.55 xxx



Specification

Part number: 1.1005.54.7xx

Temperature	
Measuring range	-30 °C ... +70 °C
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B
Rel. Humidity	
Measuring range	0 % ... 100 % rel. h.
Accuracy	± 2% rel. h. (@ 5 ... 95 % rel. h. and 10 ... 40 °C)
Meas. element	Capacitive
General	
Electr. connection	plug connection
Protection	IP 30 for sensors IP 65 for electronic
Dimension	Ø 20 x 190 mm
Weight	0.45 kg

Versions

As per 1.1005.54.7xx, but:

Product number 1.1005.54.701

Temperature	
Measuring range	-30 ... +70 °C



Accuracy	±0,1 K (PT100)
Electr. output	PT100
Rel. Humidity	
Electr. output	0 ... 1 V
General	
Power supply	6 ... 30 V DC



Product number 1.1005.54.761

Temperature	
Measuring range	-30 ... +70 °C
Accuracy	±0,2 K
Electr. output	0 ... 10 V
Rel. Humidity	
Electr. output	0 ... 10 V
General	
Power supply	15 ... 30 V DC




Product number 1.1005.54.773

Temperature	
Measuring range	-30 ... +70 °C
Accuracy	±0,2 K
Electr. output	0 ... 5 V
Rel. Humidity	
Electr. output	0 ... 5 V
General	
Power supply	10 ... 30 V DC

Accessories

Product	Product name	Brief description
	Teflonfilter with gauze ZE 20 1.1005.54.901	This hood is placed over the sensor and protects the measurement element from coarse dirt.
	Sinter Filter ZE 21 1.1005.54.902	This basket is placed over the sensor and protects the measurement element from high wind speed (>5 m/s) and increased dust. A necessity for sensors in use in exposed areas, eg. in marine climates, desert, mountains.



	Wall Holder 1.1005.54.903	<p>for mounting the temperature (2.1280.xx.xxx) or hygrothermo Sensor (1.1005..xx.xxx) onto a wall, radiation- and precipitationprotected use (for ex. indoor)</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Clamping range</td> <td>Ø 20 mm</td> </tr> <tr> <td>Mounting</td> <td>plate with with drillings 3 x Ø 6,5 mm</td> </tr> <tr> <td>Material</td> <td>plastic, grey flange</td> </tr> <tr> <td>Dimension</td> <td>96 mm lang</td> </tr> <tr> <td>Weight</td> <td>0.075 kg</td> </tr> </table>	General		Clamping range	Ø 20 mm	Mounting	plate with with drillings 3 x Ø 6,5 mm	Material	plastic, grey flange	Dimension	96 mm lang	Weight	0.075 kg						
General																				
Clamping range	Ø 20 mm																			
Mounting	plate with with drillings 3 x Ø 6,5 mm																			
Material	plastic, grey flange																			
Dimension	96 mm lang																			
Weight	0.075 kg																			
	Weather and Thermal Radiation Shield, compact 1.1025.55.000	<p>Protective case for the temperature and humidity sensors (2.1280.xx.xxx and 1.1005.54.xxx)sensor compact for outdoor installation without artificial ventilation.</p> <table border="1"> <tr> <td colspan="2">Material</td> </tr> <tr> <td>Laminations</td> <td>plastic, white</td> </tr> <tr> <td>Mast holder</td> <td>stainless stell</td> </tr> <tr> <td colspan="2">General</td> </tr> <tr> <td>Mounting</td> <td>at tube Ø 35 ... 50 mm</td> </tr> <tr> <td>Dimension</td> <td>Ø 120 x 275 mm</td> </tr> <tr> <td>Weight</td> <td>0.8 kg</td> </tr> </table>	Material		Laminations	plastic, white	Mast holder	stainless stell	General		Mounting	at tube Ø 35 ... 50 mm	Dimension	Ø 120 x 275 mm	Weight	0.8 kg				
Material																				
Laminations	plastic, white																			
Mast holder	stainless stell																			
General																				
Mounting	at tube Ø 35 ... 50 mm																			
Dimension	Ø 120 x 275 mm																			
Weight	0.8 kg																			
	Weather and Thermal Radiation Shield, compact 1.1025.55.100	<p>Protective case for the preceding temperature sensor compact for outdoor installation with artificial ventilation.</p> <table border="1"> <tr> <td colspan="2">Material</td> </tr> <tr> <td>Laminations</td> <td>plastic, white</td> </tr> <tr> <td>Mast holder</td> <td>stainless stell</td> </tr> <tr> <td colspan="2">General</td> </tr> <tr> <td>Power supply</td> <td>12V DC, 2 W</td> </tr> <tr> <td>Electr. connection</td> <td>5 m cable</td> </tr> <tr> <td>Mounting</td> <td>at tube Ø 35 ... 50 mm</td> </tr> <tr> <td>Dimension</td> <td>Ø 120 x 275 mm</td> </tr> <tr> <td>Weight</td> <td>0.8 kg</td> </tr> </table>	Material		Laminations	plastic, white	Mast holder	stainless stell	General		Power supply	12V DC, 2 W	Electr. connection	5 m cable	Mounting	at tube Ø 35 ... 50 mm	Dimension	Ø 120 x 275 mm	Weight	0.8 kg
Material																				
Laminations	plastic, white																			
Mast holder	stainless stell																			
General																				
Power supply	12V DC, 2 W																			
Electr. connection	5 m cable																			
Mounting	at tube Ø 35 ... 50 mm																			
Dimension	Ø 120 x 275 mm																			
Weight	0.8 kg																			

