

TEMPERATURE

Hygro-ThermoTransmitter

Part number: 1.1005.50.xxx

The data are output as electrical analogue signals. Humidity value is displayed additionally. The transmitters consist of a hair humidity element and a Pt 100 resistance thermometer. Sturdy construction, essential external parts are made of stainless steel. For outdoor installation we recommend the use of the weather- and thermal radiation shield order no. 1.1025.51.000.



Specification

Part number: 1.1005.50.xxx

Temperature	
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B
Rel. Humidity	
Measuring range	10 100 % rel. h.
Graduation	1 % rel. h.
Accuracy	± 3% rel. h. (@ 20 100 % rel. h. and room temperature)
Meas. element	human hairs
General	
Ambient temp.	-35 +70 °C
Scale length	94 mm (90 °)
Length	350 mm
Stem	22 mm
Stem length	250 mm
Protection	IP 65, case
Weight	0.9 kg

weight

Versions

As per 1.1005.50.xxx, but:



SCAN for more information:



Australian Sales and Support.

Email: sales@benchmarkmonitoring.com.au Website: http://www.benchmarkmonitoring.com.au/

Mobile: +(614) 01666077 Office: +(612) 65721028

Contact Benchmark Monitoring

for more information:

Address: U5 / 17 Enterprise Crescent, McDougalls Hill NSW 2330 Australia



Product number 1.1005.50.015

Rel. Humidity				
Electr. output	0 200			
General				
Electr. connection	Lemosa connector			
Product number 1.1005.50.	515			
Rel. Humidity				
Electr. output	0200	0 200		
General				
Electr. connection	3 m cable	3 m cable		

Accessories

Product	Product name	Brief description		
	Wind Protection 1.0509.85.006	Gauze- and wind protection protects the humidity measuring element from coarse dust (> 0.32 mm) and error measurements in case of wind velocities > 3 m/s. Suitable for hygro transmitter 1.1000.50.xxx.		
		General		
		Length	200 mm	
		Diameter	24 mm	
		Mesh aperture	0,32 mm	
		Material	Niro, Brass	
		Weight	0.05 kg	
	Weather and Thermal Radiation Shield 1.1025.51.000	Protective covering for the hygro-transmitter 1.1000.50.xxx for outdoor installation. Helps to prevent atmospheric influences and radiation errors from influencing the measured results.		
		General		
		Mounting	pin Ø 22 x 27 mm	
		Material	Al, galvanised and varnished	
		Dimension	Ø 170 x 450 mm	
		Weight	2.2 kg	



SCAN for more information:

Australian Sales and Support.

Email: sales@benchmarkmonitoring.com.au Website: http://www.benchmarkmonitoring.com.au/

Address: U5 / 17 Enterprise Crescent, McDougalls Hill NSW 2330 Australia

Contact Benchmark Monitoring for more information:

Mobile: +(614) 01666077 Office: +(612) 65721028