

## WIND

### Ultrasonic Anemometer 2D

Part number: 4.382x.0x.xxx

More than 35 different measurement values are available, for ex.:

- Orthogonal wind velocity vectors (X- and Y-distance)
- Scalar wind velocity
- Wind direction
- Acoustic-virtual temperature
- Acoustic-virtual temperature of the orthogonal measurement distances (X- and Y-distance)
- Standard deviation of the vectorial wind velocity (X and Y-distance)
- Standard deviation of the scalar wind velocity
- Standard deviation of the wind direction
- Standard deviation of the acoustic-virtual temperature
- Wind velocity of the gust acc. to WMO
- Wind direction of the gust acc. to WMO

The instrument is especially suitable for the use in the fields of

- Meteorology
- Climatology
- Regenerative energy, wind energy plant
- Traffic engineering, aviation and navigation
- Pollutant dispersal
- Wind alarm devices, building construction and building safety
- Indoor flow measurement
- And in alpine field of application

The ultrasonic measurement principle allows, compared to the classic anemometers, an inertia-free measurement of running variable dimensions with highest precision and accuracy. It is especially suitable for the measurement of gust- and peak values.

The measurement values can be transmitted digitally and/or in analogue form.

The serial or analogue output of the data is carried out alternatively as instantaneous value or with selectable time frame.

If necessary, the sensor arms are automatically heated in case of critical ambient temperatures. The possibility of malfunction, caused by icing, is minimized.

Model no. 4.3820.3x.xxx, thanks to the additionally installed ultrasonic converter heating, is suitable even for the more difficult use in locations where frequently icing is to be expected



## Specification

Part number: 4.382x.0x.xxx

Wind speed	
Measuring range	0 ... 85 m/s
Resolution	0.1 m/s (standard) 0.01 m/s (user defined)



Accuracy	$\pm 0.1$ m/s rms ( $\leq 5$ m/s ) $\pm 2$ % rms ( $\leq 5 \dots 85$ m/s )
<b>Wind direction</b>	
Measuring range	0 ... 360 °
Resolution	1 ° 1 ° (standard) < 1 ° (user defined)
Accuracy	$\pm 1$ ° @ WS 1 ... 60 m/s $\pm 2$ ° @ WS 60 ... 85 m/s
<b>Virtual temp.</b>	
Measuring range	-50 ... +80 °C
Resolution	0.1 K
Accuracy	$\pm 0.5$ K @ WS < 35 m/s
<b>Data output digital</b>	
Interface	RS485 / RS422
Baudrate	1200 ... 921600 Baud
Data values	instant. values, average values, standard deviation
Output range	1 per 10 msec up to 1 per 60 sec
Status signals	heating, Meas section error, Temperature of meas section
<b>Data output analog</b>	
Wind speed	0 ... 20 mA 4 ... 20 mA 0 ... 10 V 2 ... 10 V
Stromausgang	max. 400 mA
Wind direction	0 ... 20 mA 4 ... 20 mA 0 ... 10 V 2 ... 10 V
Voltage output	min. 4000 mA
Resolution	16 bit
<b>Data input analog (alternative)</b>	
Channels	3
Resolution	16bit
<b>Operating voltage</b>	
Electronic	8 ... 78 V DC or 12 ... 55 V AC / 2.5 W
Heating	24 V AC/DC, typ 80 W
<b>Heating</b>	
Heated components	Sensor arms
<b>General</b>	
Bus operation	up to 98 sensors
Electr. connection	8 pol. connector
Mounting	on a mast tube 1,5"



Housing	stainless steel (V4A) AISI316Ti
Protection	IP 67
Dimension	∅ 424 mm x 287 mm
Weight	2.5 kg

## Versions

As per 4.382x.0x.xxx, but:

Product number 4.3820.00.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Full duplex
Data telegram	no independent telegram output

Product number 4.3820.00.340

Data output digital	
Baudrate	9600 Baud
Duplex mode	Full duplex
Data telegram	VDT-Telegram (Telegram2)
Output range	10 per 1 sec

Product number 4.3820.01.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 0 ... 20 mA



Product number 4.3820.02.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 0 ... 10 V

Product number 4.3820.01.310

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 4 ... 20 mA

Product number 4.3820.01.310

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 4 ... 20 mA

Product number 4.3820.02.320

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data input analog	
Input type	3 x 0 ... 10 V

Product number 4.3820.02.323



Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data input analog	
Input type	1 x 0 ... 10 V 2 x 2 ... 10 V






Product number 4.3820.00.260

Data output digital	
Baudrate	4800 Baud
Duplex mode	Full duplex
Data telegram	NMEA - Telegram
Output range	10 per 1 sec

## Accessories

Product	Product name	Brief description																		
	Ultrasonic Bird deflector 4.3800.90.000	<p>The Ultrasonic Bird Deflector protects the ultrasonic anemometer against measurement faults, which might be caused by different species of birds.</p> <p>Data output digital</p> <table border="1"> <tr> <td>Switching output</td> <td>max. 24 V AC/DC</td> </tr> </table> <p>Interface</p> <table border="1"> <tr> <td>Type</td> <td>RS485</td> </tr> <tr> <td>Data format</td> <td>8N1</td> </tr> <tr> <td>Baud rate</td> <td>2400 ... 115200 Baud</td> </tr> </table> <p>General</p> <table border="1"> <tr> <td>Power supply</td> <td>12 ... 24V DC 24 V AC</td> </tr> <tr> <td>Electr. connection</td> <td>cable gland</td> </tr> <tr> <td>Housing</td> <td>Polycarbonate</td> </tr> <tr> <td>Protection</td> <td>IP 65</td> </tr> <tr> <td>Weight</td> <td>0.2 kg</td> </tr> </table>	Switching output	max. 24 V AC/DC	Type	RS485	Data format	8N1	Baud rate	2400 ... 115200 Baud	Power supply	12 ... 24V DC 24 V AC	Electr. connection	cable gland	Housing	Polycarbonate	Protection	IP 65	Weight	0.2 kg
Switching output	max. 24 V AC/DC																			
Type	RS485																			
Data format	8N1																			
Baud rate	2400 ... 115200 Baud																			
Power supply	12 ... 24V DC 24 V AC																			
Electr. connection	cable gland																			
Housing	Polycarbonate																			
Protection	IP 65																			
Weight	0.2 kg																			
	Device to refuse birds 507245	The device to refuse birds shall prevent smaller birds in the distance of the US transformer from sitting on the instrument, thus providing for an undisturbed operation.																		



	<b>Connecting cable</b> 50775x	Suitable cable for 4.3820/30/75/80/81  • length: see versions  <b>General</b> <table border="1"> <tr> <td>Cable length</td> <td>see versions</td> </tr> <tr> <td>Cable</td> <td>PUR 4 x 0,75 +2x2x0,14 mm<sup>2</sup></td> </tr> </table>	Cable length	see versions	Cable	PUR 4 x 0,75 +2x2x0,14 mm <sup>2</sup>				
Cable length	see versions									
Cable	PUR 4 x 0,75 +2x2x0,14 mm <sup>2</sup>									
	<b>Bird spike</b> 508396	The bird spike prevents bigger birds from resting in the measurement path between the ultrasonic transducers, providing an undisturbed operation.  <b>General</b> <table border="1"> <tr> <td>Material</td> <td>V4A (AISI 316L)</td> </tr> </table>	Material	V4A (AISI 316L)						
Material	V4A (AISI 316L)									
	<b>Northring for Ultrasonic anemometer</b> 508696	The adapter is used for the north alignment of a Ultrasonic anemometer.  <b>General</b> <table border="1"> <tr> <td>Length</td> <td>90 mm</td> </tr> <tr> <td>Material</td> <td>Aluminum anodized ( AlMgSi1 )</td> </tr> <tr> <td>Weight</td> <td>0.4 kg</td> </tr> <tr> <td>Mounting</td> <td>for mast <math>\varnothing</math> 50 mm for sensor <math>\varnothing</math> 50 mm</td> </tr> </table>	Length	90 mm	Material	Aluminum anodized ( AlMgSi1 )	Weight	0.4 kg	Mounting	for mast $\varnothing$ 50 mm for sensor $\varnothing$ 50 mm
Length	90 mm									
Material	Aluminum anodized ( AlMgSi1 )									
Weight	0.4 kg									
Mounting	for mast $\varnothing$ 50 mm for sensor $\varnothing$ 50 mm									
	<b>Meteo-Online</b> 9.1700.98.x01	Meteo-Online is a software for detecting, filing, and displaying data of meteorological measuring instruments. The display of the data is carried out graphically as diagram and/or as text. The user has the possibility to place the display-elements free on the screen, and to save them.  <b>Data display</b> <table border="1"> <tr> <td>Monitor - display</td> <td> <ul style="list-style-type: none"> <li>- Values</li> <li>- Diagrams</li> <li>- Tables</li> <li>- Windrose</li> <li>- Time</li> <li>- Date</li> </ul> </td> </tr> </table> <b>Compatibility</b> <table border="1"> <tr> <td>Connectable instruments</td> <td> <ul style="list-style-type: none"> <li>- US-Anemometer</li> <li>- Datalogger</li> <li>- Clima Sensor</li> <li>- Weather station WSC11</li> <li>- Wind display</li> <li>- etc.</li> </ul> </td> </tr> <tr> <td>System requirements</td> <td>           PC mit  <ul style="list-style-type: none"> <li>- Prozessor &gt; 1 GHz</li> <li>- RAM &gt; 1 GB</li> </ul> </td> </tr> <tr> <td>Operating system</td> <td> <ul style="list-style-type: none"> <li>- Windows 2003 SP2</li> <li>- Windows Server 2008</li> <li>- Windows 7</li> <li>- Windows Server 2008 R2</li> <li>- Windows 7 SP1</li> <li>- Windows Server 2008 R2 SP1</li> <li>- Windows 8</li> <li>- Windows 10</li> </ul> </td> </tr> </table>	Monitor - display	<ul style="list-style-type: none"> <li>- Values</li> <li>- Diagrams</li> <li>- Tables</li> <li>- Windrose</li> <li>- Time</li> <li>- Date</li> </ul>	Connectable instruments	<ul style="list-style-type: none"> <li>- US-Anemometer</li> <li>- Datalogger</li> <li>- Clima Sensor</li> <li>- Weather station WSC11</li> <li>- Wind display</li> <li>- etc.</li> </ul>	System requirements	PC mit <ul style="list-style-type: none"> <li>- Prozessor &gt; 1 GHz</li> <li>- RAM &gt; 1 GB</li> </ul>	Operating system	<ul style="list-style-type: none"> <li>- Windows 2003 SP2</li> <li>- Windows Server 2008</li> <li>- Windows 7</li> <li>- Windows Server 2008 R2</li> <li>- Windows 7 SP1</li> <li>- Windows Server 2008 R2 SP1</li> <li>- Windows 8</li> <li>- Windows 10</li> </ul>
Monitor - display	<ul style="list-style-type: none"> <li>- Values</li> <li>- Diagrams</li> <li>- Tables</li> <li>- Windrose</li> <li>- Time</li> <li>- Date</li> </ul>									
Connectable instruments	<ul style="list-style-type: none"> <li>- US-Anemometer</li> <li>- Datalogger</li> <li>- Clima Sensor</li> <li>- Weather station WSC11</li> <li>- Wind display</li> <li>- etc.</li> </ul>									
System requirements	PC mit <ul style="list-style-type: none"> <li>- Prozessor &gt; 1 GHz</li> <li>- RAM &gt; 1 GB</li> </ul>									
Operating system	<ul style="list-style-type: none"> <li>- Windows 2003 SP2</li> <li>- Windows Server 2008</li> <li>- Windows 7</li> <li>- Windows Server 2008 R2</li> <li>- Windows 7 SP1</li> <li>- Windows Server 2008 R2 SP1</li> <li>- Windows 8</li> <li>- Windows 10</li> </ul>									

