

TEMPERATURE

Ventilated air temperature transmitter

Part number: 2.1265.xx.000

The sensor is protected by a double thermal radiation shield. A built-in ventilator provides for the necessary air flow. A hanger, included in delivery, serves for the lateral mounting of the air temperature transmitter at a facade, wall etc.



Specification

Part number: 2.1265.xx.000

Temperature		
Measuring range	-30 +80 °C	
Accuracy	±0,1 K	
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B	
Time constant	17 s (90%)	
General		
Electr. connection	4 - lead circuit	
	via 4- pole clamp	
Dimension	Ø 160 H: 465 mm	
Airflow	4 6 m/s	
Weight	3.5 kg	


Versions

As per 2.1265.xx.000, but:

Product number 2.1265.20.000

General		
Power supply	12 V AC / 6 W or	
	24 V AC / 11 W or	
	24V DC / 8 W	





Australian Sales and Support.

Email: <u>sales@benchmarkmonitoring.com.au</u> Website: <u>http://www.benchmarkmonitoring.com.au/</u>

Mobile: +(614) 01666077 Office: +(612) 65721028

Contact Benchmark Monitoring

for more information:

Address: U5 / 17 Enterprise Crescent, McDougalls Hill NSW 2330 Australia



Product number 2.1265.22.000

General		
Power supply	12 V AC / 4 W	

Accessories

Product	Product name	Brief description
	Replacement- Sensor for Psychro- Transmitter 1.1130.xx 2.1266.10.001	Replacement-Sensor for Psychro-Transmitter 1.1130 compl., consisting of Pt 1000 (1/3 class B) casing and plug connection



SCAN for more information:

Australian Sales and Support.

Email: <u>sales@benchmarkmonitoring.com.au</u> Website: <u>http://www.benchmarkmonitoring.com.au/</u>

Address: U5 / 17 Enterprise Crescent, McDougalls Hill NSW 2330 Australia

Contact Benchmark Monitoring for more information:

Mobile: +(614) 01666077 Office: +(612) 65721028