

## WIND

### Wind Direction Transmitter "First Class"

**Part number: 4.3151.10.020**

Special characters are a defined and optimised, dynamic behaviour as well as:

- High level of measuring accuracy and resolution
- High damping ratio at a small delay distance
- Low starting threshold
- Very low power consumption
- No wear of the potentiometer due to mechanical stress
- Overvoltage and reverse polarity protection

The measuring value is available at the output as analogue signal. The output signal can be transmitted to display instruments, recording instruments, data loggers as well as to process control systems. For winter operation the instrument (4.3151.00.x1x) is equipped with an electronically regulated heating.



## Specification

**Part number: 4.3151.10.020**

Wind direction	
Measuring range	0 ... 360 °
Resolution	0,35 °
Accuracy	± 1 °
Starting value	< 0.5 m/s at 10 ° acc. to ASTM D 5096-96 < 0.2 m/s at 90 ° acc. to VDI3786 page 2
Distance constant	< 1.8 m acc. to ASTM D 5096-96
Damping ration	> 0.3 acc. to ASTM D 5096-96
Operating voltage	
Potent. / Elektronik	3,3 ... 12 VDC
Current consumption	0,4 mA @ 3,3V 0,5 mA @ 5V 0,8 mA @ 10V 0,9 mA @ 12V
General	
Ambient temp.	-50 °C ... +80 °C
Electr. connection	8 pol. plug connection
Mounting	on mast tube Ø 1''
Material	aluminium anodised, stainless steel






Protection	IP 55
Dimension	Ø 450 x 410 mm
Weight	0.7 kg
Fixing boring	Ø 35 x 25 mm

## Versions

No other versions of this product are available.

## Accessories

Product	Product name	Brief description														
	Traverse for Wind Transmitters "First Class" 4.3174.00.000	For mounting the wind speed transmitter and wind direction transmitter jointly onto a mast. <b>General</b> <table border="1"> <tr> <td>Height</td> <td>0.76 m</td> </tr> <tr> <td>Mounting</td> <td>on mast tube Ø 1,5"</td> </tr> <tr> <td>Material</td> <td>aluminium, anodised (AlMgSi0.5)</td> </tr> <tr> <td>Sensor distance horizontal</td> <td>0.6 m</td> </tr> <tr> <td>Sensor distance vertikal</td> <td>0.2 m</td> </tr> <tr> <td>Weight</td> <td>3 kg</td> </tr> <tr> <td>Fixing boring</td> <td>Ø 34 mm for First Class wind sensors</td> </tr> </table>	Height	0.76 m	Mounting	on mast tube Ø 1,5"	Material	aluminium, anodised (AlMgSi0.5)	Sensor distance horizontal	0.6 m	Sensor distance vertikal	0.2 m	Weight	3 kg	Fixing boring	Ø 34 mm for First Class wind sensors
Height	0.76 m															
Mounting	on mast tube Ø 1,5"															
Material	aluminium, anodised (AlMgSi0.5)															
Sensor distance horizontal	0.6 m															
Sensor distance vertikal	0.2 m															
Weight	3 kg															
Fixing boring	Ø 34 mm for First Class wind sensors															
	Hanger 1m First Class 4.3184.01.000	The hanger is used for the lateral mounting of a wind transmitter, First Class type, onto a mast <b>General</b> <table border="1"> <tr> <td>Length</td> <td>1 m</td> </tr> <tr> <td>Mounting</td> <td>at mast tube Ø 40 ... 80 mm</td> </tr> <tr> <td>Material</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Weight</td> <td>1.5 kg</td> </tr> <tr> <td>Fixing boring</td> <td>Ø 34 mm</td> </tr> </table>	Length	1 m	Mounting	at mast tube Ø 40 ... 80 mm	Material	aluminium (AlMgSi0.5)	Weight	1.5 kg	Fixing boring	Ø 34 mm				
Length	1 m															
Mounting	at mast tube Ø 40 ... 80 mm															
Material	aluminium (AlMgSi0.5)															
Weight	1.5 kg															
Fixing boring	Ø 34 mm															
	Northring for First Class Windfahne 509619	The adapter is used for the north alignment of a First Class Wind Direction Sensor. <b>General</b> <table border="1"> <tr> <td>Length</td> <td>75 mm</td> </tr> <tr> <td>Material</td> <td>Alluminum anodized (AlMgSi1)</td> </tr> <tr> <td>Weight</td> <td>0.25 kg</td> </tr> <tr> <td>Fixing boring</td> <td>for mast Ø 35 mm for sensor Ø 35 mm</td> </tr> </table>	Length	75 mm	Material	Alluminum anodized (AlMgSi1)	Weight	0.25 kg	Fixing boring	for mast Ø 35 mm for sensor Ø 35 mm						
Length	75 mm															
Material	Alluminum anodized (AlMgSi1)															
Weight	0.25 kg															
Fixing boring	for mast Ø 35 mm for sensor Ø 35 mm															

